

## 能力に影響する補正要素

### 高圧側液管の圧力損失

高圧側の圧力損失は冷凍能力の低下となります。凝縮器から膨張弁までに発生する圧力損失はフラッシュガスの発生につながり、膨張弁の能力低下となりますので通常1～3°C程度の過冷却を考慮する必要があります。

### 低圧側配管の圧力損失補正係数

分配器や蒸発器内部の圧力損失は温度の不均衡や能力低下の原因となり、また内部均圧式膨張弁では静止過熱度の増加につながります。分配器及び蒸発器中にて圧力損失が変化した場合の補正係数です。

R134a

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.987	0.973	0.960	0.946	0.932	0.917	0.903	0.888	0.873	0.858
-50	1.000	0.987	0.973	0.959	0.945	0.931	0.916	0.901	0.886	0.871	0.856
-40	1.000	0.986	0.972	0.958	0.944	0.929	0.914	0.899	0.884	0.868	0.852
-30	1.000	0.986	0.971	0.956	0.941	0.926	0.911	0.895	0.879	0.863	0.846
-20	1.000	0.985	0.969	0.954	0.938	0.922	0.905	0.888	0.871	0.854	0.836
-10	1.000	0.983	0.967	0.950	0.932	0.914	0.896	0.878	0.859	0.840	0.820
-5	1.000	0.982	0.965	0.946	0.928	0.909	0.890	0.870	0.850	0.829	0.808
0	1.000	0.981	0.962	0.942	0.922	0.902	0.881	0.860	0.838	0.815	0.792
5	1.000	0.979	0.958	0.937	0.915	0.892	0.869	0.845	0.821	0.796	0.770
10	1.000	0.977	0.953	0.929	0.904	0.879	0.852	0.825	0.797	0.768	0.738

R404A

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.993	0.985	0.978	0.970	0.962	0.955	0.947	0.939	0.931	0.923
-50	1.000	0.992	0.985	0.977	0.969	0.962	0.954	0.946	0.938	0.930	0.922
-40	1.000	0.992	0.984	0.976	0.968	0.960	0.952	0.944	0.936	0.928	0.919
-30	1.000	0.992	0.984	0.975	0.967	0.959	0.950	0.942	0.933	0.924	0.915
-20	1.000	0.991	0.983	0.974	0.965	0.956	0.947	0.937	0.928	0.919	0.909
-10	1.000	0.990	0.981	0.971	0.961	0.951	0.941	0.931	0.921	0.910	0.900
-5	1.000	0.990	0.980	0.969	0.959	0.948	0.937	0.926	0.915	0.904	0.893
0	1.000	0.989	0.978	0.967	0.955	0.944	0.932	0.920	0.908	0.896	0.884
5	1.000	0.988	0.976	0.963	0.951	0.938	0.925	0.912	0.899	0.885	0.872
10	1.000	0.986	0.973	0.959	0.945	0.930	0.916	0.901	0.886	0.870	0.855

R407C

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.992	0.985	0.977	0.969	0.961	0.953	0.945	0.937	0.929	0.921
-50	1.000	0.992	0.984	0.977	0.969	0.961	0.952	0.944	0.936	0.928	0.919
-40	1.000	0.992	0.984	0.976	0.968	0.960	0.951	0.943	0.935	0.926	0.917
-30	1.000	0.992	0.983	0.975	0.967	0.958	0.950	0.941	0.932	0.923	0.914
-20	1.000	0.991	0.983	0.974	0.965	0.956	0.947	0.938	0.929	0.919	0.910
-10	1.000	0.991	0.981	0.972	0.962	0.952	0.943	0.933	0.923	0.913	0.902
-5	1.000	0.990	0.980	0.970	0.960	0.950	0.940	0.929	0.919	0.908	0.897
0	1.000	0.990	0.979	0.968	0.958	0.947	0.936	0.925	0.913	0.902	0.890
5	1.000	0.989	0.977	0.966	0.954	0.942	0.931	0.918	0.906	0.894	0.881
10	1.000	0.988	0.975	0.963	0.950	0.937	0.924	0.910	0.897	0.883	0.869

R410A

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.994	0.989	0.983	0.977	0.972	0.966	0.960	0.954	0.949	0.943
-50	1.000	0.994	0.989	0.983	0.977	0.971	0.965	0.959	0.953	0.948	0.942
-40	1.000	0.994	0.988	0.982	0.976	0.970	0.964	0.958	0.952	0.946	0.940
-30	1.000	0.994	0.988	0.981	0.975	0.969	0.963	0.956	0.950	0.943	0.937
-20	1.000	0.993	0.987	0.980	0.973	0.967	0.960	0.953	0.946	0.939	0.932
-10	1.000	0.993	0.986	0.978	0.971	0.963	0.956	0.948	0.941	0.933	0.925
-5	1.000	0.992	0.985	0.977	0.969	0.961	0.953	0.945	0.937	0.929	0.920
0	1.000	0.992	0.983	0.975	0.966	0.958	0.949	0.940	0.932	0.923	0.914
5	1.000	0.991	0.982	0.972	0.963	0.954	0.944	0.934	0.925	0.915	0.905
10	1.000	0.990	0.979	0.969	0.958	0.948	0.937	0.926	0.915	0.904	0.892

R448A

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.993	0.986	0.978	0.971	0.964	0.956	0.949	0.941	0.934	0.926
-50	1.000	0.993	0.985	0.978	0.971	0.963	0.956	0.948	0.941	0.933	0.925
-40	1.000	0.993	0.985	0.978	0.970	0.962	0.955	0.947	0.939	0.931	0.923
-30	1.000	0.992	0.984	0.977	0.969	0.961	0.953	0.945	0.937	0.928	0.920
-20	1.000	0.992	0.984	0.975	0.967	0.959	0.950	0.942	0.933	0.924	0.916
-10	1.000	0.991	0.982	0.973	0.964	0.955	0.946	0.937	0.927	0.918	0.908
-5	1.000	0.991	0.981	0.972	0.962	0.953	0.943	0.933	0.923	0.913	0.903
0	1.000	0.990	0.980	0.970	0.960	0.950	0.939	0.929	0.918	0.908	0.897
5	1.000	0.989	0.979	0.968	0.957	0.946	0.934	0.923	0.911	0.900	0.888
10	1.000	0.988	0.976	0.965	0.952	0.940	0.928	0.915	0.902	0.889	0.876

R449A

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.993	0.986	0.978	0.971	0.963	0.956	0.948	0.941	0.933	0.925
-50	1.000	0.993	0.985	0.978	0.970	0.963	0.955	0.948	0.940	0.932	0.924
-40	1.000	0.992	0.985	0.977	0.970	0.962	0.954	0.946	0.938	0.930	0.922
-30	1.000	0.992	0.984	0.976	0.969	0.960	0.952	0.944	0.936	0.928	0.919
-20	1.000	0.992	0.984	0.975	0.967	0.958	0.950	0.941	0.932	0.923	0.915
-10	1.000	0.991	0.982	0.973	0.964	0.955	0.945	0.936	0.927	0.917	0.907
-5	1.000	0.991	0.981	0.972	0.962	0.952	0.942	0.933	0.922	0.912	0.902
0	1.000	0.990	0.980	0.970	0.960	0.949	0.939	0.928	0.917	0.906	0.895
5	1.000	0.989	0.978	0.967	0.956	0.945	0.934	0.922	0.910	0.899	0.887
10	1.000	0.988	0.976	0.964	0.952	0.939	0.927	0.914	0.901	0.888	0.875

R407H

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.993	0.985	0.978	0.970	0.963	0.955	0.947	0.939	0.932	0.924
-50	1.000	0.993	0.985	0.977	0.970	0.962	0.954	0.946	0.939	0.931	0.923
-40	1.000	0.992	0.985	0.977	0.969	0.961	0.953	0.945	0.937	0.929	0.921
-30	1.000	0.992	0.984	0.976	0.968	0.960	0.952	0.943	0.935	0.926	0.918
-20	1.000	0.992	0.983	0.975	0.966	0.958	0.949	0.940	0.931	0.922	0.913
-10	1.000	0.991	0.982	0.973	0.964	0.954	0.945	0.935	0.926	0.916	0.906
-5	1.000	0.991	0.981	0.971	0.962	0.952	0.942	0.932	0.922	0.912	0.901
0	1.000	0.990	0.980	0.970	0.959	0.949	0.938	0.928	0.917	0.906	0.895
5	1.000	0.989	0.978	0.967	0.956	0.945	0.933	0.922	0.910	0.898	0.886
10	1.000	0.988	0.976	0.964	0.952	0.939	0.927	0.914	0.901	0.888	0.874

R463A-J

蒸発温度 (°C)	圧力損失 (MPa)										
	0	0.025	0.05	0.075	0.1	0.125	0.15	0.175	0.2	0.225	0.25
-60	1.000	0.995	0.990	0.984	0.979	0.974	0.969	0.963	0.958	0.953	0.947
-50	1.000	0.995	0.990	0.984	0.979	0.974	0.968	0.963	0.957	0.952	0.946
-40	1.000	0.995	0.989	0.984	0.978	0.973	0.967	0.962	0.956	0.951	0.945
-30	1.000	0.994	0.989	0.983	0.978	0.972	0.966	0.960	0.955	0.949	0.943
-20	1.000	0.994	0.988	0.982	0.976	0.970	0.964	0.958	0.952	0.946	0.940
-10	1.000	0.994	0.987	0.981	0.975	0.968	0.962	0.955	0.948	0.942	0.935
-5	1.000	0.993	0.987	0.980	0.973	0.966	0.960	0.953	0.946	0.939	0.932
0	1.000	0.993	0.986	0.979	0.972	0.964	0.957	0.950	0.942	0.935	0.927
5	1.000	0.992	0.985	0.977	0.970	0.962	0.954	0.946	0.938	0.930	0.922
10	1.000	0.992	0.984	0.975	0.967	0.958	0.950	0.941	0.932	0.923	0.915

## CTX 能力表

CTX- R134a		蒸発温度 (°C)	冷凍能力 (kW)						R404A						
形式	番号		凝縮温度 (°C)						カタログ番号						
			30	35	38	40	45	50	30	35	38	40	45	50	
34006BM 34006DM	34013BM 34013DM	10	2.34	2.49	2.58	2.61	2.73	2.79	-5	2.06	2.04	2.01	1.97	1.88	1.75
		0	2.21	2.29	2.35	2.37	2.41	2.43	-10	1.88	1.84	1.81	1.77	1.67	1.53
		-5	2.07	2.13	2.19	2.20	2.21	2.22	-20	1.56	1.53	1.50	1.45	1.36	1.21
		-10	1.86	1.93	1.97	1.98	2.00	1.98	-30	1.25	1.20	1.16	1.12	1.04	-
		-20	1.44	1.50	1.51	1.51	1.51	1.49	-40	0.94	0.90	0.87	0.83	0.76	-
	34023BM 34023DM	-30	1.36	1.38	1.40	1.40	1.40	1.37	-5	4.40	4.38	4.33	4.26	4.05	3.74
		10	5.33	5.79	6.00	6.11	6.34	6.43	-10	4.18	4.12	4.05	3.97	3.74	3.42
		0	4.66	4.90	5.01	5.05	5.16	5.21	-20	3.61	3.51	3.42	3.34	3.11	2.80
		-5	4.22	4.37	4.45	4.49	4.54	4.59	-30	3.10	2.99	2.90	2.82	2.59	-
		-10	3.88	3.97	4.02	4.05	4.07	4.07	-40	2.59	2.45	2.37	2.30	2.08	-
34035BM 34035DM	34045BM 34045DM	-20	3.22	3.24	3.28	3.27	3.28	3.27	-5	8.16	8.08	7.97	7.86	7.46	6.90
		-30	2.59	2.80	2.93	2.93	2.93	2.90	-10	7.23	7.10	6.98	6.85	6.46	5.95
		10	9.29	10.1	10.4	10.6	11.0	11.3	-20	6.25	6.07	5.92	5.78	5.38	4.88
		0	8.32	9.09	8.92	9.00	9.19	9.26	-30	5.13	4.92	4.78	4.65	4.27	-
		-5	7.57	7.85	7.99	8.05	7.79	8.18	-40	4.00	3.81	3.68	3.56	3.25	-
	34045DM	-10	6.72	6.92	7.01	7.05	7.11	7.09	-5	11.7	11.6	11.5	11.2	10.7	9.03
		-20	5.84	5.95	6.00	6.02	6.02	5.95	-10	10.8	10.6	10.4	10.2	9.67	8.87
		-30	5.34	5.41	5.45	5.44	5.44	5.37	-20	9.14	8.88	8.65	8.46	7.87	7.14
		10	14.3	15.5	16.0	16.3	16.9	17.4	-30	7.69	7.41	7.19	6.99	6.44	-
		0	12.7	13.3	13.6	13.7	14.0	14.1	-40	6.01	5.73	5.53	5.36	4.88	-
57060DM	57080DM	-10	10.6	10.9	11.0	11.1	11.2	11.2	-5	15.0	14.9	14.8	14.5	13.8	12.7
		-20	9.22	9.42	9.49	9.51	9.54	9.47	-10	13.8	13.6	13.4	13.1	12.4	11.4
		-30	8.06	8.15	8.20	8.19	8.19	8.08	-20	11.7	11.3	11.1	10.8	10.1	9.18
		10	18.5	19.8	20.6	20.8	21.6	22.3	-30	9.88	9.52	9.23	8.98	8.27	-
		0	16.2	17.0	17.4	17.4	17.8	18.0	-40	7.72	7.37	7.10	6.89	6.27	-
	71110DM	-5	15.2	15.7	16.2	16.2	16.4	16.4	-5	20.5	20.4	20.1	19.7	18.8	17.4
		-10	13.6	14.0	14.2	14.1	14.3	14.3	-10	19.2	18.9	18.6	18.2	17.2	15.8
		-20	11.9	12.1	12.2	12.2	12.2	12.2	-20	16.3	15.9	15.5	15.1	14.0	12.7
		-30	10.8	10.9	10.9	11.0	11.0	10.9	-30	13.8	13.3	12.9	12.5	11.5	-
		10	24.5	26.5	27.6	27.9	29.1	29.8	-40	11.5	11.0	10.7	10.3	9.42	-
71140DM	71160DM	0	22.0	22.9	23.6	23.7	24.2	24.4	-5	27.3	27.1	26.8	26.3	25.0	23.2
		-5	20.5	21.2	21.5	21.6	21.9	22.0	-10	25.7	25.4	24.9	24.5	23.1	21.1
		-10	18.8	19.3	19.7	19.8	20.0	19.9	-20	21.8	21.2	20.7	20.1	18.8	17.0
		-20	15.6	15.8	15.9	15.9	16.0	15.8	-30	18.5	17.8	17.3	16.8	15.4	-
		-30	14.2	14.3	14.4	14.4	14.4	14.2	-40	15.4	14.8	14.3	13.8	12.5	-
	12220DM	10	32.3	34.9	36.3	36.9	38.4	39.3	-5	38.7	38.4	38.0	37.3	35.5	32.7
		0	29.0	30.5	31.2	31.5	32.0	32.2	-10	35.5	34.5	34.0	33.3	31.4	29.1
		-5	27.0	28.1	28.6	28.8	29.2	29.2	-20	31.4	30.5	29.7	28.9	27.0	24.5
		-10	24.5	25.4	25.7	25.7	27.2	25.9	-30	26.2	25.1	24.4	23.7	21.8	-
		-20	20.7	21.1	21.3	21.3	21.3	21.2	-40	22.0	20.9	20.2	19.5	17.8	-
12270DM	12330DU	-30	18.8	19.0	19.1	19.2	19.1	18.8	-5	48.5	48.2	47.6	46.8	44.5	41.1
		10	43.5	47.1	48.8	49.7	51.6	52.8	-10	45.6	45.0	44.2	43.4	40.9	37.5
		0	40.2	42.0	43.0	43.4	44.3	44.7	-20	39.3	38.1	37.2	36.4	33.8	30.7
		-5	37.1	38.5	39.2	39.5	39.9	40.0	-30	32.9	31.6	30.7	29.8	27.4	-
		-10	33.8	34.8	35.2	35.5	35.7	35.6	-40	28.0	26.7	25.7	24.8	22.6	-
	12420DU	-20	27.8	28.1	28.6	28.7	28.7	28.6	-5	55.2	54.7	54.0	53.2	50.5	46.8
		-30	25.6	25.9	26.1	26.2	26.1	25.7	-10	51.6	50.7	49.8	48.9	46.2	42.4
		10	55.4	59.9	62.1	63.3	65.7	67.1	-20	44.7	43.5	42.4	41.5	38.6	34.9
		0	51.3	53.7	54.9	55.5	56.5	57.0	-30	37.4	36.0	34.4	34.1	31.2	-
		-5	47.3	49.0	49.8	50.0	50.6	50.0	-40	31.9	30.3	29.5	28.6	25.8	-
12330DM	12420DU	-10	42.6	43.8	44.4	44.5	45.0	44.0	-5	76.0	75.4	74.5	73.4	69.6	64.4
		-20	35.0	37.1	37.4	37.4	37.3	37.0	-10	71.1	70.0	68.8	67.5	63.7	58.5
		-30	31.6	32.0	32.2	32.3	32.1	31.7	-20	60.7	59.0	57.5	56.2	52.3	47.3
		10	63.8	69.2	71.8	72.9	75.0	76.2	-30	51.7	49.7	48.2	46.9	43.1	-
		0	58.4	61.3	62.6	63.3	64.4	64.0	-40	43.7	41.7	40.2	38.9	35.4	-
	12500DU	-5	53.6	55.7	56.6	57.1	57.7	58.0	-5	93.7	93.1	91.9	90.5	85.9	79.4
		-10	48.5	50.2	50.9	51.2	51.6	51.0	-10	87.4	86.0	84.6	83.1	78.3	71.8
		-20	41.3	42.1	42.6	42.6	42.7	42.0	-20	75.0	72.9	71.0	69.5	64.6	58.5
		-30	36.2	36.5	36.8	36.9	36.8	36.3	-30	63.6	61.2	59.3	57.7	53.1	-
		10	90.8	98.4	102	104	108	110	-40	53.6	51.1	49.3	47.8	43.5	-
12420DM	12500DU	0	71.2	83.5	85.2	86.2	87.9	88.5	-5	114	112	112	109	104	96.4
		-5	90.5	94.0	95.6	96.3	97.3	97.8	-10	107	106	104	102	95.9	88.0
		-10	81.8	84.7	85.7	86.3	87.0	86.8	-20	91.5	88.9	86.6	84.7	78.8	71.3
		-20	68.5	69.9	70.5	70.6	70.8	70.1	-30	77.6	74.7	72.4	70.4	64.9	-
		-30	62.6	63.3	63.7	63.8	63.6	62.8	-40	65.4	62.4	60.1	58.3	53.1	-
	12500DM	10	109	117	122	124	129	133	-5	150	148	147	144	137	127
		0	97.8	102	105	106	108	109	-10	142	140	137	134	127	116
		-5	90.5	94.0	95.6	96.3	97.3	97.8	-20	122	118	116	113	106	95.6
		-10	81.8	84.7	85.7	86.3	87.0	86.8	-30	104	100	97.1	94.5	87.0	-
		-30	84.0	85.6	86.3	86.5	86.6	85.9	-40	88.6	84.4	81.4	78.8	71.8	-
12500DM	12500DU	10	100	103	105	105	106	106	-5	179	177	175	172	163	151
		0</													

## R407C

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)						
形式	番号		凝縮温度 (°C)						
			30	35	38	40	45	50	
CTX-	34006BP	0	3.15	3.27	3.32	3.34	3.37	3.36	
		-5	3.07	3.13	3.17	3.18	3.19	3.14	
		-10	2.81	2.49	2.91	2.91	2.91	2.86	
		-20	2.40	2.43	2.44	2.43	2.41	2.37	
		-30	1.96	1.95	1.96	1.95	1.94	-	
	34006DP	-40	1.64	1.61	1.61	1.61	1.57	-	
		0	6.62	6.90	7.01	7.06	7.12	7.08	
		-5	6.03	6.19	6.27	6.28	6.30	6.25	
		-10	5.80	5.05	5.93	5.93	5.92	5.85	
		-20	5.08	5.13	5.15	5.14	5.10	4.99	
CTX-	34013BP	-30	4.50	4.51	4.51	4.49	4.43	-	
		-40	3.90	3.88	3.88	3.86	3.79	-	
		0	11.4	11.9	12.1	12.1	12.2	12.2	
		-5	10.9	11.3	11.4	11.4	11.5	11.3	
		-10	9.80	9.99	10.1	10.1	10.1	9.86	
	34023BP	-20	8.69	8.75	8.78	8.75	8.68	8.51	
		-30	7.34	7.34	7.34	7.31	7.21	-	
		-40	5.90	5.90	5.89	5.86	5.76	-	
		0	17.6	18.1	18.5	18.8	18.7	-	
		-5	16.1	16.4	16.7	16.7	16.8	16.6	
CTX-	34035BP	-10	14.9	15.2	15.3	15.2	15.3	15.1	
		-20	12.9	13.0	13.0	13.0	12.8	12.6	
		-30	11.2	11.3	11.2	11.2	11.0	-	
		-40	9.07	9.07	9.05	9.00	8.85	-	
	34045BP	0	22.5	23.4	23.8	23.9	24.1	24.0	
		-5	20.7	21.2	21.5	21.5	21.6	21.4	
		-10	19.2	19.5	19.6	19.6	19.5	19.4	
		-20	16.5	16.6	16.7	16.6	16.5	16.2	
		-30	14.3	14.4	14.4	14.4	14.2	-	
CTX-	34045DP	-40	11.7	11.7	11.6	11.6	11.4	-	
		0	31.2	32.4	33.0	33.1	33.5	33.3	
		-5	29.1	30.0	30.3	30.3	30.5	30.2	
		-10	27.5	28.1	28.3	28.2	28.3	27.9	
		-20	23.9	24.1	24.2	24.0	23.9	23.4	
	57060DP	-30	20.8	20.8	20.8	20.7	20.5	-	
		-40	18.1	18.0	18.0	18.0	17.6	-	
		0	41.9	43.5	44.2	44.4	44.9	44.6	
		-5	38.7	39.7	40.2	40.3	40.4	40.0	
		-10	36.8	37.5	37.8	37.8	37.7	37.2	
CTX-	57080DP	-20	31.8	32.2	32.2	32.2	31.8	31.2	
		-30	27.9	28.0	27.9	27.8	27.4	-	
		-40	24.1	24.0	24.0	23.9	23.4	-	
		0	58.1	60.3	61.3	61.7	62.1	61.8	
		-5	54.5	55.9	56.6	56.8	56.9	56.4	
	71110DP	-10	50.5	51.5	51.9	52.0	51.8	51.2	
		-20	45.7	46.1	46.2	46.1	45.6	44.8	
		-30	39.3	39.3	39.3	39.1	38.6	-	
		-40	34.1	34.1	34.1	33.9	33.4	-	
		0	72.7	75.5	76.7	77.1	77.8	77.4	
CTX-	71140DP	-5	68.2	69.6	70.4	70.7	70.9	70.5	
		-10	64.7	66.1	66.5	66.5	66.4	65.6	
		-20	57.1	57.6	57.8	57.6	57.1	56.0	
		-30	49.2	49.4	49.4	49.1	48.5	-	
		-40	43.3	43.3	43.2	43.2	42.2	-	
	71160DP	0	84.0	87.2	88.5	89.0	89.8	89.5	
		-5	78.1	80.3	81.2	81.4	81.6	80.8	
		-10	73.6	75.1	75.7	75.7	75.5	74.5	
		-20	64.9	66.1	66.2	66.1	65.4	64.2	
		-30	56.3	56.8	56.5	56.2	55.5	-	
CTX-	12220DP	-40	49.6	49.8	49.5	49.3	48.4	-	
		0	115	120	122	122	123	123	
		-5	108	111	112	112	113	111	
		-10	102	104	105	104	103	-	
		-20	88.8	89.6	89.8	89.7	88.8	87.0	
	12270DP	-30	77.7	78.1	78.0	77.7	76.6	-	
		-40	68.2	68.2	68.0	67.7	66.6	-	
		0	140	145	148	149	150	150	
		-5	132	134	136	136	136	135	
		-10	124	125	127	126	126	126	
CTX-	12330DP	-20	108	110	110	110	109	106	
		-30	94.5	94.9	94.8	94.4	93.1	-	
		-40	82.7	82.7	82.5	82.1	80.8	-	
		0	172	178	182	184	183	-	
		-5	161	164	167	167	168	166	
	12420DP	-10	152	155	157	156	154	-	
		-20	133	135	135	134	133	131	
		-30	116	117	116	116	114	-	
		-40	101	101	101	101	99.0	-	
		0	222	231	234	235	237	236	
CTX-	12500DP	-5	210	216	218	218	219	217	
		-10	200	203	206	206	204	203	
		-20	178	179	180	179	178	175	
		-30	155	155	155	154	152	-	
		-40	136	136	137	136	133	-	
	12500DC1	0	266	277	282	283	285	284	
		-5	253	259	262	263	264	261	
		-10	241	246	248	248	248	244	
		-20	214	214	216	214	213	209	
		-30	186	187	187	186	184	-	
		-40	165	164	164	163	160	-	

## R448A

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)						
形式	番号		凝縮温度 (°C)						
			30	35	38	40	45	50	
CTX-	34006BC1	0	2.91	3.02	3.02	3.04	3.02	2.99	
		-5	2.83	2.87	2.87	2.88	2.83	2.80	
		-10	2.49	2.53	2.53	2.52	2.48	2.45	
		-20	1.96	1.94	1.93	1.92	1.87	1.82	
		-30	1.58	1.56	1.56	1.54	1.50	-	
	34006DC1	-40	1.31	1.28	1.27	1.26	1.21	-	
		0	5.98	6.25	6.26	6.29	6.25	6.17	
		-5	5.62	5.75	5.74	5.66	5.56	-	
		-10	5.02	5.10	5.08	5.08	4.99	4.89	
		-20	4.15	4.19	4.16	4.14	4.02	3.92	
CTX-	34013BC1	-30	3.62	3.61	3.57	3.54	3.43	-	
		-40	3.12	3.08	3.05	3.03	2.91	-	
		0	10.3	10.7	10.7	10.8	10.7	10.6	
		-5	9.79	10.0	10.0	10.0	9.86	9.64	
		-10	8.40	8.53	8.50	8.48	8.33	8.19	
	34013DC1	-20	7.30	7.37	7.30	7.27	7.07	6.88	
		-30	5.90	5.88	5.82	5.78	5.59	-	
		-40	4.71	4.68	4.63	4.59	4.43	-	
		0	15.7	16.3	16.4	16.4	16.4	16.1	
		-5	15.5	15.7	15.7	15.5	15.2	-	
CTX-	34035BC1	-10	13.3	13.4	13.4	13.3	13.1	12.9	
		-20	11.7	11.7	11.6	11.6	11.2	11.0	
		-30	8.97	9.01	8.87	8.88	8.52	-	
		-40	7.25	7.20	7.11	7.05	6.80	-	
	34045BC1	0	20.2	21.1	21.1	21.2	21.0	20.7	
		-5	20.0	20.3	20.2	20.1	19.9	19.6	
		-10	16.9	17.3	17.3	17.2	16.8	16.5	
		-20	14.8	14.9	14.9	14.8	14.4	14.0	
		-30	11.5	11.5	11.5	11.4	11.0	-	
CTX-	34045DC1	-40	9.35	9.29	9.15	9.08	8.78	-	

R449A

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)						
形式	番号		凝縮温度 (°C)						
			30	35	38	40	45	50	
CTX-	34006BC1	0	2.87	2.95	2.98	3.00	2.99	2.94	
		-5	2.70	2.73	2.76	2.75	2.73	2.69	
		-10	2.46	2.48	2.49	2.48	2.45	2.41	
		-20	1.93	1.91	1.90	1.89	1.85	1.79	
		-30	1.55	1.54	1.53	1.52	1.49	-	
	34013BC1	-40	1.29	1.25	1.25	1.23	1.19	-	
		0	5.91	6.12	6.18	6.20	6.18	6.08	
		-5	5.37	5.48	5.51	5.50	5.46	5.35	
		-10	4.95	5.00	5.01	5.00	4.93	4.81	
		-20	4.09	4.11	4.10	4.07	3.98	3.85	
CTX-	34023BC1	-30	3.57	3.55	3.52	3.48	3.40	-	
		-40	3.07	3.02	3.00	2.97	2.87	-	
		0	10.2	10.5	10.6	10.7	10.6	10.4	
		-5	9.35	9.47	9.55	9.56	9.51	9.27	
		-10	8.29	8.36	8.37	8.36	8.24	8.05	
	34035BC1	-20	7.20	7.24	7.20	7.16	7.00	6.77	
		-30	5.82	5.77	5.73	5.68	5.53	-	
		-40	4.64	4.60	4.55	4.51	4.37	-	
		0	15.5	15.9	16.2	16.1	16.2	15.9	
		-5	14.8	14.9	15.0	15.1	14.9	14.6	
CTX-	34045BC1	-10	13.1	13.1	13.3	13.1	13.0	12.7	
		-20	11.5	11.5	11.5	11.4	11.1	10.8	
		-30	8.84	8.84	8.73	8.73	8.43	-	
		-40	7.13	7.07	6.99	6.92	6.72	-	
		0	20.0	20.7	20.8	20.9	20.8	20.3	
	34045DC1	-5	19.1	19.3	19.4	19.3	19.2	18.8	
		-10	16.7	16.9	17.0	17.0	16.6	16.2	
		-20	14.6	14.7	14.7	14.5	14.3	13.8	
		-30	11.3	11.3	11.3	11.2	10.9	-	
		-40	9.20	9.11	9.00	8.91	8.67	-	
CTX-	57060DC1	0	27.9	28.7	29.0	29.1	29.0	28.5	
		-5	25.9	26.5	26.6	26.6	26.4	25.9	
		-10	24.0	24.2	24.3	24.2	23.8	23.3	
		-20	19.8	19.8	19.7	19.6	19.2	18.6	
		-30	16.4	16.4	16.3	16.1	15.7	-	
		-40	14.2	14.1	14.0	13.8	13.4	-	
	57080DC1	0	37.0	38.2	38.6	38.6	38.7	37.9	
		-5	34.5	35.2	35.4	35.5	35.1	34.4	
		-10	31.5	30.5	30.6	30.5	30.2	30.6	
		-20	26.5	26.6	26.5	26.4	25.7	24.9	
		-30	22.1	21.9	21.8	21.6	21.0	-	
CTX-	71110DC1	-40	19.0	18.7	18.5	18.4	17.8	-	
		0	51.0	52.4	53.0	53.2	53.0	52.2	
		-5	47.1	47.9	48.2	48.2	47.8	46.7	
		-10	43.1	43.5	43.6	43.5	42.9	41.8	
		-20	35.8	35.7	35.6	35.3	34.6	33.4	
		-30	31.1	30.9	30.7	30.4	29.6	-	
		-40	26.8	26.6	26.4	26.1	25.3	-	
	71140DC1	0	64.8	66.9	67.6	67.7	67.6	66.4	
		-5	59.9	60.9	61.3	61.3	60.8	59.4	
		-10	54.1	54.8	54.9	54.7	54.0	52.5	
		-20	46.5	46.6	46.4	46.1	45.2	43.7	
		-30	39.0	38.8	38.5	38.1	37.2	-	
CTX-	71160DC1	-40	34.1	33.7	33.4	33.3	32.0	-	
		0	74.4	76.8	77.5	77.7	77.6	76.2	
		-5	68.6	70.0	70.3	70.3	69.7	68.1	
		-10	62.4	63.2	63.3	63.2	62.3	60.6	
		-20	53.3	53.3	53.1	52.8	51.6	49.9	
		-30	44.6	44.4	44.1	43.7	42.5	-	
		-40	39.0	38.7	38.3	37.9	36.7	-	
	12220DC1	0	101	104	105	105	105	103	
		-5	94.4	96.6	97.3	97.4	96.0	93.5	
		-10	86.0	87.1	87.2	86.9	85.8	83.5	
		-20	71.8	71.9	71.6	71.1	69.6	67.3	
		-30	61.5	61.3	60.8	60.4	58.7	-	
CTX-	12270DC1	-40	53.6	53.1	52.6	52.0	50.5	-	
		0	123	126	128	128	129	126	
		-5	115	117	117	117	116	114	
		-10	104	105	107	106	104	101	
		-20	87.3	87.4	87.1	86.6	84.8	81.9	
		-30	74.9	74.5	74.0	73.4	71.4	-	
		-40	65.0	64.4	63.8	63.1	61.3	-	
	12330DC1	0	151	155	157	158	157	155	
		-5	141	143	144	145	143	140	
		-10	129	130	130	129	128	125	
		-20	107	108	108	107	104	101	
		-30	91.6	91.7	90.5	90.5	87.4	-	
CTX-	12420DC1	-40	79.7	79.1	78.2	77.4	75.1	-	
		0	192	197	200	200	200	197	
		-5	180	184	186	185	184	180	
		-10	162	164	165	164	161	157	
		-20	137	137	137	136	132	129	
		-30	123	121	121	120	117	-	
		-40	107	106	105	101	-	-	
	12500DC1	0	231	237	240	239	239	237	
		-5	217	220	223	222	220	214	
		-10	194	196	197	196	193	188	
		-20	165	165	165	163	160	155	
		-30	147	147	146	145	141	-	
CTX-	12500DC2	-40	129	127	126	125	121	-	
		0	274	292	240	239	305	312	
		-5	265	276	285	289	291	293	
		-10	255	265	271	273	275	276	
		-20	239	241	245	243	244	242	
	12500DC2	-30	210	213	214	214	214	-	
		-40	191	192	193	193	193	-	

R407H

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)						
形式	番号		凝縮温度 (°C)						
			30	35	38	40	45	50	
CTX-	34006DC2	0	3.25	3.44	3.59	3.65	3.68	3.74	
		-5	3.21	3.34	3.45	3.49	3.52	3.52	
		-10	2.98	2.68	3.19	3.21	3.23	3.23	
		-20	2.68	2.73	2.76	2.76	2.75	2.75	
		-30	2.21	2.22	2.25	2.24	2.26	-	
	34013DC2	-40	1.90	1.88	1.90	1.91	1.89	-	
		0	6.82	7.27	7.57	7.71	7.78	7.88	
		-5	6.31	6.60	6.82	6.89	6.95	7.01	
		-10	6.14	5.44	6.49	6.54	6.58	6.61	
		-20	5.68	5.77	5.83	5.83	5.84	5.79	
CTX-	34023DC2	-30	4.50	4.54	4.58	4.57	4.56	-	
		0	11.8	12.5	13.1	13.2	13.3	13.6	
		-5	11.4	12.0	12.4	12.5	12.7	12.7	
		-10	10.4	10.8	11.1	11.2	11.1	-	
		-20	9.71	9.84	9.94	9.95	9.87	-	
	34035DC2	-30	8.28	8.35	8.41	8.40	8.40	-	
		0	18.1	19.1	20.0	20.2	20.6	20.8	
		-5	16.9	17.5	18.2	18.3	18.5	18.6	
		-10	15.8	16.4	16.7	16.8	17.0	17.1	
		-20	14.4	14.6	14.7	14.8	14.6	-	
CTX-	34045DC2	-30	12.6	12.9	12.8	12.9	12.8	-	
		0	23.2	24.7	25.7	26.1	26.3	26.7	
		-5	21.7	22.6	23.4	23.6	23.8	24.0	
		-10	20.3	21.0	21.5	21.6	21.7	21.9	
		-2							

## R404A (ホットガスバイパス用)

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)								
			入口側圧力 (MPa)								
形式	番号		1.32 (30°C相当)		1.70 (40°C相当)		2.22 (50°C相当)				
			ホットガス温度 (°C)								
CTX-	34006BU	0	0.37	0.37	0.35	0.45	0.42	0.42	0.53	0.50	
		-10	0.37	0.35	0.35	0.42	0.42	0.40	0.60	0.50	
		-20	0.35	0.35	0.35	0.42	0.40	0.40	0.60	0.47	
		-30	0.35	0.35	0.32	0.40	0.40	0.37	0.47	0.45	
		-40	0.35	0.32	0.32	0.40	0.37	0.37	0.45	0.42	
	34013BU	0	0.77	0.75	0.72	0.87	0.87	0.82	1.05	1.02	
		-10	0.75	0.72	0.72	0.87	0.85	0.82	1.02	1.00	
		-20	0.72	0.72	0.70	0.82	0.80	0.80	1.00	0.97	
		-30	0.72	0.70	0.67	0.80	0.80	0.77	0.95	0.92	
		-40	0.70	0.67	0.65	0.80	0.75	0.75	0.92	0.90	
CTX-	34023BU	0	1.32	1.27	1.25	1.52	1.47	1.42	1.80	1.74	
		-10	1.30	1.25	1.22	1.47	1.42	1.40	1.73	1.70	
		-20	1.25	1.22	1.17	1.42	1.37	1.35	1.68	1.63	
		-30	1.22	1.17	1.15	1.37	1.35	1.30	1.63	1.58	
		-40	1.17	1.15	1.12	1.35	1.30	1.25	1.58	1.52	
	34035BU	0	1.87	1.82	1.78	2.14	2.07	2.02	2.52	2.47	
		-10	1.82	1.78	1.73	2.07	2.02	2.68	2.44	2.39	
		-20	1.78	1.73	1.68	2.02	1.95	1.92	2.37	2.32	
		-30	1.73	1.68	1.63	1.95	1.9	1.85	2.29	2.22	
		-40	1.68	1.63	1.58	1.9	1.82	1.78	2.22	2.14	
CTX-	34045BU	0	2.40	2.34	2.27	2.78	2.68	2.59	3.24	3.17	
		-10	2.34	2.27	2.22	2.68	2.59	2.54	3.15	3.07	
		-20	2.27	2.20	2.14	2.59	2.49	2.47	3.05	2.99	
		-30	2.22	2.14	2.09	2.49	2.44	2.37	2.95	2.85	
		-40	2.14	2.07	2.02	2.44	2.34	2.27	2.85	2.78	
	57060DU	0	2.95	2.85	2.78	3.34	3.27	3.17	3.97	3.87	
		-10	2.88	2.80	2.70	3.27	3.17	3.10	3.85	3.75	
		-20	2.80	2.70	2.63	3.17	3.07	3.00	3.75	3.61	
		-30	2.70	2.63	2.54	3.07	3.00	2.90	3.70	3.50	
		-40	2.63	2.54	2.47	2.97	2.88	2.80	3.46	3.37	
CTX-	57080DU	0	3.80	3.68	3.56	4.31	4.05	4.03	5.11	5.00	
		-10	3.70	3.60	3.49	4.22	4.12	4.00	4.97	4.85	
		-20	3.60	3.49	3.39	4.10	3.97	3.87	4.82	4.66	
		-30	3.49	3.39	3.29	3.97	3.85	3.75	4.64	4.52	
		-40	3.39	3.29	3.20	3.85	3.73	3.61	4.47	4.35	
	71110DU	0	4.52	4.37	4.25	5.15	5.02	4.85	6.09	5.94	
		-10	4.39	4.27	4.15	5.02	4.87	4.75	5.89	5.77	
		-20	4.27	4.15	4.05	4.85	4.72	4.59	5.72	5.57	
		-30	4.15	4.02	3.92	4.72	4.57	4.44	5.52	5.37	
		-40	4.02	3.90	3.80	4.64	4.42	4.30	5.32	5.17	
CTX-	71140DU	0	5.49	5.32	5.20	6.27	6.10	5.92	7.38	7.24	
		-10	5.34	5.20	5.05	6.09	5.94	5.77	7.17	7.02	
		-20	5.20	5.05	4.92	5.92	5.74	5.59	6.97	6.77	
		-30	5.05	4.90	4.77	5.74	5.57	5.42	6.74	6.54	
		-40	4.90	4.77	4.62	5.54	5.37	5.22	6.47	6.29	
	71160DU	0	6.44	6.24	6.07	7.31	7.17	6.94	8.66	8.52	
		-10	6.27	6.09	5.91	7.17	6.97	6.77	8.45	8.24	
		-20	6.09	5.92	5.77	6.94	6.74	6.57	8.17	7.95	
		-30	5.92	5.74	5.59	6.74	6.54	6.37	7.88	7.67	
		-40	5.74	5.59	5.42	6.52	6.29	6.14	7.60	7.38	
CTX-	12220DU	0	8.95	8.59	8.31	10.1	9.80	9.59	12.0	11.7	
		-10	8.66	8.45	8.17	9.80	9.59	9.30	11.6	11.3	
		-20	8.45	8.17	7.95	9.59	9.23	9.09	11.2	10.9	
		-30	8.17	7.95	7.74	9.23	9.02	8.73	10.9	10.6	
		-40	7.95	7.67	7.46	9.02	8.66	8.45	10.5	10.2	
	12270DU	0	10.9	10.5	10.2	12.4	12.1	11.7	14.6	14.3	
		-10	10.6	10.3	10.0	12.1	11.7	11.4	14.2	13.9	
		-20	10.3	10.0	9.73	11.7	11.3	11.1	13.8	13.4	
		-30	10.0	9.66	9.44	11.3	11.0	10.7	13.3	12.9	
		-40	9.66	9.44	9.16	11.0	10.7	10.3	12.8	12.5	
CTX-	12330DU	0	13.1	12.7	12.4	15.0	14.6	14.2	17.7	17.3	
		-10	12.8	12.4	12.1	14.6	14.2	13.8	17.1	16.8	
		-20	12.4	12.1	11.7	14.2	13.7	13.4	16.6	16.1	
		-30	12.1	11.7	11.4	13.7	13.3	13.0	16.1	15.6	
		-40	11.7	11.3	11.1	13.2	12.8	12.5	15.4	15.1	
	12420DU	0	14.8	14.3	13.9	16.8	16.3	15.8	19.9	19.4	
		-10	14.3	14.0	13.6	16.3	15.9	15.4	19.3	18.8	
		-20	14.0	13.6	13.2	15.8	15.4	15.1	18.7	18.2	
		-30	13.6	13.1	12.8	15.4	15.0	14.6	18.1	17.6	
		-40	13.1	12.8	12.5	15.0	14.5	14.1	17.3	16.9	
CTX-	12500DU	0	15.6	15.1	14.7	17.7	17.3	16.8	21.0	20.5	
		-10	15.1	14.7	14.3	17.3	16.8	16.3	20.3	19.8	
		-20	14.7	14.3	13.9	16.8	16.8	15.8	19.7	19.2	
		-30	14.3	13.9	13.6	16.3	15.8	15.3	19.0	18.6	
		-40	13.9	13.5	13.1	15.7	15.2	14.8	18.3	17.8	

R448A (ホットガスバイパス用)

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)									
			入口側圧力 (MPa)									
			1.32 (30°C相当)			1.70 (40°C相当)			2.22 (50°C相当)			
形式	番号	ホットガス温度 (°C)										
CTX-	34006BC1 34006DC1	0	0.53	0.52	0.50	0.62	0.60	0.59	0.70	0.68	0.66	
		-10	0.51	0.50	0.49	0.60	0.58	0.57	0.67	0.65	0.63	
		-20	0.50	0.48	0.47	0.57	0.56	0.54	0.64	0.62	0.60	
		-30	0.48	0.46	0.45	0.55	0.53	0.52	0.61	0.59	0.57	
		-40	0.46	0.44	0.43	0.52	0.51	0.49	0.57	0.56	0.54	
	34013BC1 34013DC1	0	1.06	1.03	1.00	1.24	1.21	1.17	1.40	1.36	1.32	
		-10	1.03	1.00	0.97	1.20	1.16	1.13	1.34	1.30	1.27	
		-20	0.99	0.96	0.94	1.15	1.12	1.09	1.28	1.24	1.21	
		-30	0.95	0.93	0.90	1.10	1.07	1.04	1.21	1.18	1.15	
		-40	0.91	0.89	0.86	1.05	1.02	0.99	1.15	1.12	1.09	
CTX-	34023BC1 34023DC1	0	1.80	1.75	1.70	2.10	2.04	1.98	2.36	2.29	2.23	
		-10	1.74	1.69	1.64	2.02	1.96	1.91	2.26	2.20	2.14	
		-20	1.68	1.63	1.59	1.94	1.89	1.84	2.16	2.10	2.04	
		-30	1.61	1.57	1.52	1.86	1.80	1.76	2.05	1.99	1.94	
		-40	1.55	1.50	1.46	1.77	1.72	1.67	1.94	1.89	1.84	
	34035BC1 34035DC1	0	2.53	2.46	2.39	2.96	2.87	2.79	3.33	3.23	3.14	
		-10	2.45	2.38	2.32	2.85	2.77	2.69	3.19	3.10	3.01	
		-20	2.36	2.30	2.23	2.74	2.66	2.59	3.05	2.96	2.88	
		-30	2.27	2.21	2.15	2.62	2.54	2.47	2.89	2.81	2.73	
		-40	2.18	2.12	2.06	2.50	2.42	2.36	2.74	2.66	2.59	
CTX-	34045BC1 34045DC1	0	3.13	3.04	2.95	3.65	3.54	3.45	4.11	3.99	3.88	
		-10	3.03	2.94	2.86	3.52	3.42	3.32	3.94	3.83	3.72	
		-20	2.92	2.83	2.76	3.38	3.28	3.19	3.76	3.65	3.55	
		-30	2.81	2.72	2.65	3.23	3.14	3.05	3.57	3.47	3.38	
		-40	2.69	2.61	2.54	3.08	2.99	2.91	3.38	3.28	3.19	
	57060DC1	0	3.97	3.86	3.75	4.63	4.50	4.38	5.22	5.07	4.93	
		-10	3.84	3.73	3.63	4.47	4.34	4.22	5.00	4.86	4.73	
		-20	3.71	3.60	3.50	4.29	4.17	4.05	4.78	4.64	4.51	
		-30	3.56	3.46	3.37	4.10	3.99	3.88	4.54	4.41	4.29	
		-40	3.42	3.32	3.23	3.91	3.80	3.70	4.29	4.17	4.05	
CTX-	57080DC1	0	5.11	4.96	4.83	5.97	5.80	5.64	6.72	6.52	6.35	
		-10	4.95	4.80	4.67	5.75	5.59	5.43	6.44	6.25	6.08	
		-20	4.77	4.63	4.51	5.52	5.37	5.22	6.15	5.97	5.81	
		-30	4.59	4.46	4.33	5.28	5.13	4.99	5.84	5.67	5.52	
		-40	4.40	4.27	4.15	5.04	4.89	4.76	5.52	5.36	5.22	
	71110DC1	0	6.08	5.91	5.74	7.10	6.89	6.71	7.99	7.76	7.55	
		-10	5.88	5.71	5.56	6.84	6.65	6.47	7.66	7.44	7.24	
		-20	5.68	5.51	5.36	6.57	6.38	6.21	7.31	7.10	6.91	
		-30	5.46	5.30	5.16	6.29	6.11	5.94	6.95	6.75	6.56	
		-40	5.23	5.08	4.94	5.99	5.82	5.66	6.57	6.38	6.21	
CTX-	71140DC1	0	7.41	7.20	7.00	8.65	8.40	8.17	9.73	9.45	9.20	
		-10	7.17	6.96	6.77	8.34	8.10	7.88	9.34	9.07	8.82	
		-20	6.92	6.72	6.53	8.01	7.78	7.57	9.91	8.65	8.42	
		-30	6.65	6.46	6.28	7.66	7.44	7.24	8.47	8.22	8.00	
		-40	6.37	6.19	6.02	7.30	7.09	6.90	8.01	7.78	7.56	
	71160DC1	0	8.67	8.43	8.20	10.1	9.84	9.57	11.4	11.1	10.8	
		-10	8.39	8.15	7.93	9.76	9.48	9.22	10.9	10.6	10.3	
		-20	8.10	7.87	7.65	9.38	9.11	8.86	10.4	10.1	9.86	
		-30	7.79	7.56	7.36	8.97	8.71	8.47	9.91	9.63	9.37	
		-40	7.46	7.25	7.05	8.55	8.30	8.08	9.37	9.10	8.86	
CTX-	12220DC1	0	11.9	11.6	11.3	13.9	13.5	13.2	15.7	15.2	14.8	
		-10	11.6	11.2	10.9	13.4	13.1	12.7	15.0	14.6	14.2	
		-20	11.1	10.8	10.5	12.9	12.5	12.2	14.4	14.0	13.6	
		-30	10.7	10.4	10.1	12.3	12.0	11.7	13.6	13.3	12.9	
		-40	10.3	9.98	9.71	11.8	11.4	11.1	12.9	12.5	12.2	
	12270DC1	0	14.6	14.2	13.8	17.0	16.5	16.1	19.2	18.6	18.1	
		-10	14.1	13.7	13.3	16.4	15.9	15.5	18.4	17.8	17.4	
		-20	13.6	13.2	12.9	15.8	15.3	14.9	17.5	17.0	16.6	
		-30	13.1	12.7	12.4	15.1	14.6	14.2	16.7	16.2	15.7	
		-40	12.5	12.2	11.9	14.4	14.0	13.6	15.8	15.3	14.9	
CTX-	12230DC1	0	17.6	17.1	16.6	20.5	20.0	19.4	23.1	22.5	21.8	
		-10	17.0	16.5	16.1	19.8	19.2	18.7	22.2	21.5	21.0	
		-20	16.4	16.0	15.5	19.0	18.5	18.0	21.2	20.6	20.0	
		-30	15.8	15.3	14.9	18.2	17.7	17.2	20.1	19.5	19.0	
		-40	15.1	14.7	14.3	17.3	16.8	16.4	19.0	18.5	18.0	
	12420DC1	0	19.8	19.2	18.7	23.1	22.5	21.9	26.0	25.3	24.6	
		-10	19.2	18.6	18.1	22.3	21.7	21.1	25.0	24.3	23.6	
		-20	18.5	18.0	17.5	21.4	20.8	20.2	23.8	23.2	22.5	
		-30	17.8	17.3	16.8	20.5	19.9	19.4	22.6	22.0	21.4	
		-40	17.1	16.6	16.1	19.5	19.0	18.5	21.4	20.8	20.2	
CTX-	12500DC1	0	20.9	20.3	19.7	24.4	23.7	23.0	27.4	26.6	25.9	
		-10	20.2	19.6	19.1	23.5	22.8	22.2	26.3	25.6	24.9	
		-20	19.5	18.9	18.4	22.6	21.9	21.3	25.1	24.4	23.7	
		-30	18.7	18.2	17.7	21.6	21.0	20.4	23.9	23.2	22.5	
		-40	18.0	17.4	17.0	20.6	20.0	19.4	22.6	21.9	21.3	

R449A (ホットガスバイパス用)

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)								
			入口側圧力 (MPa)								
			1.32 (30°C相当)			1.70 (40°C相当)			2.22 (50°C相当)		
形式	番号		ホットガス温度 (°C)								
			60	80	100	60	80	100	60	80	100
CTX-	34006BC1 34006DC1	0	0.54	0.53	0.51	0.63	0.61	0.60	0.71	0.69	0.67
		-10	0.52	0.51	0.49	0.61	0.59	0.57	0.68	0.66	0.64
		-20	0.50	0.49	0.48	0.58	0.57	0.55	0.65	0.63	0.61
		-30	0.48	0.47	0.46	0.56	0.54	0.53	0.62	0.60	0.58
		-40	0.46	0.45	0.44	0.53	0.52	0.50	0.58	0.56	0.55
	34013BC1 34013DC1	0	1.09	1.06	1.03	1.27	1.23	1.20	1.42	1.38	1.35
		-10	1.05	1.02	0.99	1.22	1.19	1.15	1.36	1.33	1.29
		-20	1.01	0.98	0.96	1.17	1.14	1.11	1.30	1.26	1.23
		-30	0.97	0.95	0.92	1.12	1.09	1.06	1.24	1.20	1.17
		-40	0.93	0.91	0.88	1.07	1.04	1.01	1.17	1.13	1.10
CTX-	34023BC1 34023DC1	0	1.85	1.79	1.74	2.15	2.09	2.03	2.42	2.35	2.28
		-10	1.79	1.73	1.69	2.07	2.01	1.96	2.32	2.25	2.19
		-20	1.72	1.67	1.63	1.99	1.93	1.88	2.21	2.15	2.09
		-30	1.65	1.61	1.56	1.90	1.85	1.80	2.10	2.04	1.98
		-40	1.59	1.54	1.50	1.81	1.76	1.71	1.98	1.93	1.87
	34035BC1 34035DC1	0	2.60	2.53	2.46	3.03	2.94	2.86	3.41	3.31	3.22
		-10	2.52	2.44	2.38	2.92	2.84	2.76	3.27	3.17	3.09
		-20	2.43	2.36	2.29	2.80	2.72	2.65	3.12	3.03	2.94
		-30	2.33	2.26	2.20	2.68	2.60	2.53	2.96	2.87	2.79
		-40	2.23	2.17	2.11	2.55	2.48	2.41	2.79	2.71	2.64
CTX-	34045BC1 34045DC1	0	3.21	3.12	3.03	3.74	3.63	3.54	4.21	4.08	3.97
		-10	3.11	3.02	2.93	3.61	3.50	3.41	4.03	3.92	3.81
		-20	3.00	2.91	2.83	3.46	3.36	3.27	3.85	3.74	3.63
		-30	2.88	2.80	2.72	3.31	3.21	3.13	3.65	3.55	3.45
		-40	2.76	2.68	2.60	3.15	3.06	2.98	3.45	3.35	3.26
	57060DC1	0	4.08	3.96	3.85	4.75	4.62	4.49	5.34	5.19	5.05
		-10	3.94	3.83	3.73	4.58	4.45	4.33	5.12	4.97	4.84
		-20	3.80	3.69	3.59	4.40	4.27	4.15	4.88	4.74	4.62
		-30	3.66	3.55	3.45	4.20	4.08	3.97	4.64	4.50	4.38
		-40	3.50	3.40	3.31	4.00	3.89	3.78	4.38	4.25	4.14
CTX-	57080DC1	0	5.25	5.10	4.96	6.12	5.94	5.78	6.88	6.68	6.50
		-10	5.08	4.93	4.80	5.90	5.73	5.57	6.59	6.40	6.23
		-20	4.90	4.76	4.63	5.66	5.50	5.35	6.29	6.11	5.94
		-30	4.71	4.57	4.45	5.41	5.25	5.11	5.97	5.80	5.64
		-40	4.51	4.38	4.26	5.15	5.00	4.87	5.64	5.48	5.33
	71110DC1	0	6.24	6.06	5.90	7.28	7.07	6.88	8.18	7.94	7.73
		-10	6.04	5.87	5.71	7.01	6.81	6.63	7.84	7.62	7.41
		-20	5.83	5.66	5.50	6.73	6.54	6.36	7.48	7.27	7.07
		-30	5.60	5.44	5.29	6.44	6.25	6.08	7.10	6.90	6.71
		-40	5.36	5.21	5.07	6.13	5.95	5.79	6.71	6.51	6.34
CTX-	71140DC1	0	7.61	7.39	7.19	8.87	8.61	8.38	9.97	9.68	9.42
		-10	7.36	7.15	6.95	8.55	8.30	8.07	9.55	9.28	9.03
		-20	7.10	6.89	6.71	8.20	7.97	7.75	9.12	8.85	8.61
		-30	6.82	6.62	6.44	7.84	7.62	7.41	8.65	8.40	8.18
		-40	6.53	6.35	6.17	7.47	7.25	7.06	8.17	7.94	7.72
	71160DC1	0	8.91	8.65	8.42	10.4	10.1	9.81	11.7	11.3	11.0
		-10	8.62	8.37	8.14	10.0	9.72	9.45	11.2	10.9	10.6
		-20	8.31	8.07	7.85	9.61	9.33	9.08	10.7	10.4	10.1
		-30	7.99	7.76	7.55	9.18	8.92	8.68	10.1	9.84	9.57
		-40	7.65	7.43	7.23	8.74	8.49	8.26	9.57	9.29	9.04
CTX-	12220DC1	0	12.3	11.9	11.6	14.3	13.9	13.5	16.1	15.6	15.2
		-10	11.9	11.5	11.2	13.8	13.4	13.0	15.4	15.0	14.6
		-20	11.4	11.1	10.8	13.2	12.8	12.5	14.7	14.3	13.9
		-30	11.0	10.7	10.4	12.6	12.3	11.9	13.9	13.5	13.2
		-40	10.5	10.2	9.95	12.0	11.7	11.4	13.2	12.8	12.4
	12270DC1	0	15.0	14.5	14.2	17.5	17.0	16.5	19.6	19.1	18.5
		-10	14.5	14.1	13.7	16.8	16.3	15.9	18.8	18.3	17.8
		-20	14.0	13.6	13.2	16.1	15.7	15.3	17.9	17.4	17.0
		-30	13.4	13.0	12.7	15.4	15.0	14.6	17.0	16.5	16.1
		-40	12.9	12.5	12.2	14.7	14.3	13.9	16.1	15.6	15.2
CTX-	12230DC1	0	18.1	17.6	17.1	21.1	20.5	19.9	23.7	23.0	22.4
		-10	17.5	17.0	16.5	20.3	19.7	19.2	22.7	22.0	21.4
		-20	16.9	16.4	15.9	19.5	18.9	18.4	21.7	21.0	20.5
		-30	16.2	15.7	15.3	18.6	18.1	17.6	20.6	20.0	19.4
		-40	15.5	15.1	14.7	17.7	17.2	16.8	19.4	18.9	18.3
	12420DC1	0	20.4	19.8	19.2	23.7	23.0	22.4	26.7	25.9	25.2
		-10	19.7	19.1	18.6	22.9	22.2	21.6	25.6	24.8	24.1
		-20	19.0	18.4	17.9	21.9	21.3	20.7	24.4	23.7	23.0
		-30	18.2	17.7	17.2	21.0	20.4	19.8	23.1	22.5	21.9
		-40	17.5	17.0	16.5	20.0	19.4	18.9	21.9	21.2	20.7
CTX-	12500DC1	0	21.4	20.8	20.3	25.0	24.3	23.6	28.1	27.3	26.5
		-10	20.7	20.2	19.6	24.1	23.4	22.8	26.9	26.2	25.4
		-20	20.0	19.4	18.9	23.1	22.5	21.8	25.7	25.0	24.3
		-30	19.2	18.7	18.2	22.1	21.5	20.9	24.4	23.7	23.0
		-40	18.4	17.9	17.4	21.1	20.4	19.9	23.0	22.4	21.8

R407H (ホットガスバイパス用)

カタログ番号		蒸発温度 (°C)	冷凍能力 (kW)								
			入口側圧力 (MPa)								
			1.32 (30°C相当)			1.70 (40°C相当)			2.22 (50°C相当)		
形式	番号		ホットガス温度 (°C)								
			60	80	100	60	80	100	60	80	100
CTX-	34006BC1 34006DC1	0	0.59	0.57	0.56	0.70	0.68	0.66	0.81	0.79	0.76
		-10	0.57	0.56	0.54	0.68	0.66	0.64	0.78	0.76	0.74
		-20	0.56	0.54	0.53	0.66	0.64	0.62	0.75	0.73	0.71
		-30	0.54	0.52	0.51	0.64	0.62	0.60	0.72	0.70	0.68
		-40	0.52	0.50	0.49	0.61	0.59	0.58	0.69	0.67	0.65
	34013BC1 34013DC1	0	1.18	1.14	1.11	1.40	1.36	1.32	1.62	1.57	1.53
		-10	1.15	1.11	1.08	1.36	1.32	1.29	1.56	1.52	1.48
		-20	1.11	1.08	1.05	1.32	1.28	1.24	1.51	1.46	1.42
		-30	1.08	1.05	1.02	1.27	1.23	1.20	1.45	1.41	1.37
		-40	1.04	1.01	0.98	1.22	1.19	1.15	1.39	1.35	1.31
CTX-	34023BC1 34023DC1	0	1.99	1.93	1.88	2.37	2.30	2.24	2.73	2.66	2.58
		-10	1.94	1.88	1.83	2.30	2.24	2.17	2.64	2.57	2.50
		-20	1.88	1.83	1.78	2.23	2.16	2.10	2.55	2.48	2.41
		-30	1.82	1.77	1.72	2.15	2.09	2.03	2.45	2.38	2.31
		-40	1.76	1.71	1.66	2.07	2.01	1.95	2.34	2.28	2.21
	34035BC1 34035DC1	0	2.80	2.72	2.65	3.34	3.24	3.16	3.85	3.74	3.64
		-10	2.73	2.65	2.58	3.24	3.15	3.06	3.73	3.62	3.52
		-20	2.65	2.57	2.50	3.14	3.05	2.96	3.59	3.49	3.39
		-30	2.56	2.49	2.42	3.03	2.94	2.86	3.45	3.35	3.26
		-40	2.48	2.41	2.34	2.91	2.83	2.75	3.30	3.21	3.12
CTX-	34045BC1 34045DC1	0	3.46	3.36	3.27	4.12	4.00	3.90	4.75	4.62	4.49
		-10	3.37	3.27	3.18	4.00	3.89	3.78	4.60	4.47	4.35
		-20	3.27	3.18	3.09	3.87	3.76	3.66	4.43	4.31	4.19
		-30	3.17	3.08	2.99	3.74	3.63	3.53	4.26	4.14	4.02
		-40	3.06	2.97	2.89	3.59	3.49	3.40	4.07	3.96	3.85
	57060DC1	0	4.40	4.27	4.15	5.24	5.08	4.95	6.04	5.86	5.71
		-10	4.28	4.16	4.04	5.08	4.94	4.80	5.84	5.67	5.52
		-20	4.15	4.03	3.92	4.92	4.78	4.65	5.63	5.47	5.32
		-30	4.02	3.91	3.80	4.75	4.61	4.48	5.41	5.25	5.11
		-40	3.88	3.77	3.67	4.57	4.43	4.31	5.17	5.03	4.89
CTX-	57080DC1	0	5.66	5.50	5.35	6.74	6.55	6.37	7.77	7.55	7.35
		-10	5.51	5.35	5.20	6.54	6.36	6.18	7.52	7.30	7.11
		-20	5.35	5.19	5.05	6.33	6.15	5.98	7.25	7.04	6.85
		-30	5.18	5.03	4.89	6.11	5.93	5.77	6.96	6.76	6.58
		-40	5.00	4.86	4.72	5.88	5.71	5.55	6.66	6.47	6.29
	71110DC1	0	6.73	6.54	6.36	8.02	7.79	7.58	9.25	8.98	8.74
		-10	6.55	6.36	6.19	7.78	7.56	7.36	8.95	8.69	8.45
		-20	6.36	6.18	6.01	7.53	7.32	7.12	8.62	8.38	8.15
		-30	6.16	5.98	5.82	7.27	7.06	6.87	8.28	8.04	7.82
		-40	5.95	5.78	5.62	6.99	6.79	6.61	7.92	7.70	7.49
CTX-	71140DC1	0	8.20	7.97	7.75	9.77	9.49	9.23	11.3	10.9	10.6
		-10	7.98	7.76	7.54	9.49	9.21	8.96	10.9	10.6	10.3
		-20	7.75	7.53	7.32	9.18	8.92	8.67	10.5	10.2	9.93
		-30	7.50	7.29	7.09	8.86	8.60	8.37	10.1	9.80	9.53
		-40	7.25	7.04	6.85	8.52	8.27	8.05	9.66	9.38	9.12
	71160DC1	0	9.60	9.33	9.07	11.4	11.1	10.8	13.2	12.8	12.5
		-10	9.35	9.08	8.83	11.1	10.8	10.5	12.8	12.4	12.1
		-20	9.08	8.81	8.58	10.7	10.4	10.2	12.3	11.9	11.6
		-30	8.79	8.53	8.30	10.4	10.1	9.80	11.8	11.5	11.2
		-40	8.49	8.24	8.02	9.98	9.69	9.43	11.3	11.0	10.7
CTX-	12220DC1	0	13.2	12.8	12.5	15.7	15.3	14.9	18.2	17.6	17.2
		-10	12.9	12.5	12.2	15.3	14.8	14.4	17.6	17.1	16.6
		-20	12.5	12.1	11.8	14.8	14.4	14.0	16.9	16.4	16.0
		-30	12.1	11.7	11.4	14.3	13.9	13.5	16.3	15.8	15.4
		-40	11.7	11.3	11.04	13.7	13.3	13.0	15.6	15.1	14.7
	12270DC1	0	16.1	15.7	15.3	19.2	18.7	18.2	22.2	21.5	21.0
		-10	15.7	15.3	14.9	18.7	18.1	17.6	21.5	20.8	20.3
		-20	15.3	14.8	14.4	18.1	17.5	17.1	20.7	20.1	19.5
		-30	14.8	14.3	14.0	17.4	16.9	16.5	19.9	19.3	18.8
		-40	14.3	13.9	13.5	16.8	16.3	15.8	19.0	18.5	18.0
CTX-	12230DC1	0	19.5	18.9	18.4	23.2	22.5	21.9	26.8	26.0	25.3
		-10	19.0	18.4	17.9	22.5	21.9	21.3	25.9	25.2	24.5
		-20	18.4	17.9	17.4	21.8	21.2	20.6	25.0	24.2	23.6
		-30	17.8	17.3	16.8	21.0	20.4	19.9	24.0	23.3	22.6
		-40	17.2	16.7	16.3	20.2	19.7	19.1	22.9	22.3	21.7
	12420DC1	0	21.9	21.3	20.7	26.1	25.4	24.7	30.1	29.3	28.5
		-10	21.4	20.7	20.2	25.4	24.6	24.0	29.2	28.3	27.6
		-20	20.7	20.1	19.6	24.6	23.8	23.2	28.1	27.3	26.6
		-30	20.1	19.5	19.0	23.7	23.0	22.4	27.0	26.2	25.5
		-40	19.4	18.8	18.3	22.8	22.1	21.5	25.8	25.1	24.4
CTX-	12500DC1	0	23.1	22.5	21.8	27.5	26.7	26.0	31.8	30.8	30.0
		-10	22.5	21.9	21.3	26.7	26.0	25.3	30.7	29.8	29.0
		-20	21.8	21.2	20.6	25.9	25.1	24.4	29.6	28.8	28.0
		-30	21.2	20.5	20.0	25.0	24.2	23.6	28.4	27.6	26.9
		-40	20.4	19.8	19.3	24.0	23.3	22.7	27.2	26.4	25.7